



## Velluto

Special stucco with iridescent effect can reproduce the look of velvet in its various shades and give walls an unparalleled atmosphere. The available colours are obtained by mixing a VELLUTO metallic base with the required amount of dye, called COLOUR KIT.

**Surface preparation:** the surface must be dry and mature. Clean the surfaces to be treated by removing and loose or flaking material. Apply, at a time interval of 5-6 hours from one another, two uniformizing layers of PRELUDIO, diluted to 25-30% volume with pure water.

**Application:** apply the first layer of VELLUTO using a code 1009 stainless steel trowel and work it criss-cross in all directions to achieve shimmering shades and recreate the velvet effect on the wall. If necessary, repeat the same procedure as for the first coat when the surface is dry.

PRELUDIO spreading rate : 8-10m<sup>2</sup>/litre per coat.

VELLUTO yield 4.5-6.5m<sup>2</sup>/ litre, per coat.

COLOUR KIT packs of 100 millilitres.

The ambient temperature during the application cycle must be between 5°C and 35°C, the relative humidity must not exceed 80%. During application, avoid direct contact with skin and eyes, use clean water for dilutions, store the undiluted product in its closed packaging in a cool and dry place. The colours available are approximately and can vary from one batch to another. As the application of this product is not under our constant control. We do not consider ourselves responsible for the final result. We recommend testing the product on a small area before decorating the wall.