



## Venezia V

Venezia V, Venetian stucco. Special decorative stucco, ready to use, for interiors, gives a unique decorative finish. The smooth, mellow product is easy to apply and with the proper application technique the marble effect that resembles the stucco present in ancient Venetian palaces can be produced.

**Preparing the substrate:** The substrate must be completely dry. Clean the surfaces to be treated by removing any loose or flaking material. Apply one coat of PRELUDIO diluted by 25-30% of pure water. After 5-6 hours at 20°, proceed with the application of VENEZIA V.

PRELUDIO spreading rate: 8 - 10 m<sup>2</sup>/litre, per coat.

**Application of Venezia V:** Spread a layer of VENEZIA V using a stainless-steel trowel code: 1009. After about 5 hours at 20° apply a second coat of VENEZIA V, wait a few minutes to allow the absorption of excess water then rough up and smooth the surface with the stainless-steel trowel to obtain the desired effect.

Yield Venezia V has a spreading rate of 4 - 6m<sup>2</sup>/litre per coat.

Venezia V is available in a single base BIANCO W (White), Venezia V Bianco W (white) pack: 1 litre, 4 litres or 14 litres. COLOUR KIT pack of 100 millilitres. The colour available are obtained by mixing the product with the indicated amount of dye in the COLOUR KIT.

**Tips:** The ambient temperature during the application cycle must be between 5°C and 35°C, the relative humidity must not exceed 80%. During application avoid direct contact with skin and eyes, use clean water for diluting, store the undiluted product in its closed packaging in a cool, dry place.

The colours available are approximately and can vary from one batch to another. Since the application of the product is not under our constant control, we are not liable for the final result. We recommend testing the product on a small area before decorating the wall.